

Image shown above 118.11 with round canopy

± Ø130 - 146mm

Series	118
Mounting	Ceiling mounted
Glass Colours	White or bronze
Lamp	1W LED, 2700K, 100lm (2500K and 3000K options available)
Coaxial Length	3000mm standard / up to 30500mm maximum Adjustable length: 118.1 - 118.9 Non-adjustable length: 118.11 - 118.28
Canopy Finishes	118.1 - 118.7: white, black or brushed nickel canopy 118.1m: white, black, brushed nickel, or brushed brass canopy 118.9 - 118.28: white canopy
Materials	Blown glass, braided metal coaxial cable, electrical components, steel canopy
Power Supply	Integral Remote mounted for 118.1m Bocci recommends remote mounting power supplies for ease of long-term maintenance.
Environment	Indoor, dry location. IP30
Note	Every single Bocci product is handmade. Each one is variously blown, poured, carved, polished, packed and dispatched directly by us. As such, no two products are identical; they are individual, irregular expressions of our research.
Patent #	Worldwide patents pending.
Certifications	



Weight (kg)



Round

118.1	3.3
118.3	9.7
118.5	16.1
118.7	22.4
118.11	42.7
118.20	76.5



Square


118.11	42.7
118.16	62.5
118.28	102



Rectangle


118.9	33.7
118.11	42.7
118.16	62.5
118.20	76.5
118.28	102

ADJUSTABLE LENGTH



up to 3000
standard
up to 30500
custom

NON-ADJUSTABLE LENGTH



up to 3000
standard
up to
30500
custom

Best practices for wiring multiple single pendant fixtures with remote mounted power supplies:

- Multiple single pendant fixtures should be wired in parallel. DO NOT wire in series.
- Bocci recommends a home run line for each fixture location to avoid significant voltage drop.
- Calculations for distance to the power supply, or required wire gauge in order to avoid voltage drop, are the responsibility of the installing party.

All dimensions are in millimeters (mm) unless otherwise specified.